

tesa® Adhesive Strips for Wallpaper & Plaster – 77770 / 77771

Double sided, die-cuts without backing as refill pack to reuse the tesa® Adhesive Nails for Wallpaper & Plaster.

Main Application

tesa® Adhesive Strips for Wallpaper & Plaster are suitable for the reversible fixation of UV impermeable and sufficiently firm objects with textured and sensitive surfaces such as wallpaper or plaster.

For optimal results:

- Preparation: Clean the surfaces with rubbing alcohol and work on/ with flat, dry, dust and grease-free materials.
- Application: When affixing the strip on the wall and the object on the strip, press down firmly and evenly on the entire strip/ object for at least five seconds to secure the bond.
- Removal: Objects that are fixed with tesa® Adhesive Strips for Wallpaper & Plaster can be removed without a trace. Hold the strip by its tab and slowly pull it down parallel to the wall without pressing it against the surface.

Please note:

- Do not touch the adhesive area of the adhesive pads.
- Not suitable for use on vinyl wallpaper and anti-stick surfaces.
- Glass cleaners for preparing the surface could reduce the holding power (contains e.g. silicones: Silicone prevents an adhesive bonding and cannot be removed from surfaces with cleaners).

Technical Data & Properties

Dimensions	77770: 20 mm x 61 mm; 77771: 20 mm x 80 mm
Product Structure	3 layer
Colour	White
Thickness without liner	1,35 mm
Adhesive	Synthetic rubber
Backing	White PE-foam
Top Cover	White double sided siliconised paper with red tesa logo
Bottom Cover	White one sided siliconised paper
Storage Time	24 months
Application Temperature	Min. 15 °C
Temperature Resistance	5 – 35 °C
UV Resistance	No
Humidity Resistance	No
Holding Power	77770: 0,5kg; 77771: 1kg

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



77770



77771

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.